

ReTac®

Smooth 150

Our 6 mil (150µ), white polymeric printable PVC film with ReTac® ultra removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.

Dimensionally stable, ReTac® Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. And, with ReTac® on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed.

- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

6
mil

White
Phthalate-Free
Polymeric
PVC



Matte or Gloss



(Eco) Solvent
Latex
UV



ReTac® ultra removable
and re-positionable
adhesive



Widths up to 61 in



5 YEARS DURABILITY
INTERIOR AND EXTERIOR
(2 YEAR REMOVABILITY EXTERIOR)

EASY APPLICATION AND REMOVAL



APPLICATIONS

Smooth Flat Surfaces
Point Of Sale Graphics
Interior Décor
Decals & Stickers

Certified for
HP Latex Inks

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

ReTac®

Smooth 150

ReTac® Smooth 150 is a 6 mil (150µ) printable matte or gloss white, phthalate-free polymeric PVC film, coated on one side with ReTac® ultra removable adhesive. The adhesive is protected by a single-sided, siliconized PE coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac® Smooth 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- PHTHALATE-FREE FILM
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUES AND WALL MURALS
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, AND GLASS
- RETAC SMOOTH 150 HAS SEVERAL FIRE RATINGS, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal, for more information please contact your local representative.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

0513/2022

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte or Gloss White Polymeric PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive technology
Release Liner	88# (143gsm) 1 side siliconized PE coated Kraft paper

PRODUCT CHARACTERISTICS

Film Thickness	6 mil (150µ) 6.9 mil (172µ)
Adhesive Layer	0.9 mil (22µ) (172µ)
Outdoor Durability	5 years; 2 years removability
Application Temperature	>41°F (5°C)
Service Temperature Range	20°F to 120°F (-6.7°C to 48.9°C)
Fire Ratings	Class 0 (BS 476 - Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102) Class A or 1 (ASTM E-84)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using ReTac® Smooth 150, an overlaminate can be used for maximum life expectancy. Products recommended for use with ReTac® Smooth 150 are Drytac's Interlam™ Pro overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com