

# ReTac®

## ChalkMate®

ReTac® ChalkMate® has a traditional black chalkboard finish that can be used with standard chalk or liquid chalk markers. It utilises ReTac® ultra removable adhesive technology to create impromptu chalkboard walls that are easy to apply, re-position and remove without surface damage. It can be installed on most smooth surfaces. A second version is available that features a permanent, pressure sensitive acrylic adhesive, making it ideal for fixture applications. Both versions can also be used to make unique, custom chalkboard decals from die cut shapes or designs.

- IDEAL FOR INDOOR CHALK BOARDS
- SUITABLE FOR SCHOOLS
- CAN BE EASILY REPOSITIONED & REMOVED

Product Code: CKM-R

**125** Black  
micron Chalkboard  
PVC

Black Matte



Printers that use  
white ink  
UV



Ultra removable and  
re-positionable  
adhesive



Widths up to 1550mm

USE STANDARD CHALK OR LIQUID CHALK MARKERS

# BBQ Grill Menu

Swiches	4.75
Chicken	6.20
Steaks	12.85
Wraps	14.60
Burgers	3.15
A la Carte	21.45



### APPLICATIONS

CHALK BOARDS

RETAIL NOTICE BOARDS

MENUS & PRICE LISTS



# DRYTAC®

ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# ReTac®

## ChalkMate®

ReTac® ChalkMate® is a 125µ (5 mil) durable, printable PVC film with a traditional black chalkboard finish and ReTac® ultra removable adhesive. ReTac® ChalkMate® can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

It works well when creating chalkboard walls or making unique, custom chalkboard decals from die cut shapes or designs. Installs on most smooth surfaces.

- IDEAL FOR IN STORE PROMOTIONS
- SUITABLE FOR INTERIOR USE
- RETAC® CHALKMATE® HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Black PVC
<b>Adhesive</b>	ReTac® ultra removable and re-positionable adhesive
<b>Release Liner</b>	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	5 mil (125µ)   5.8 mil
<b>Adhesive Layer</b>	0.8 mil (20µ)   (145µ)
<b>Film/Adhesive Ratio</b>	5:0.8
<b>UV Protection Factor</b>	Not Applicable
<b>Outdoor Durability</b>	Not Applicable
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	-4°F to 203°F (-20°C to 95°C)
<b>Flame Retardancy</b>	Class 0 BS 476 - Part 6 & 7 Fire Rating
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Special Regulatory Information:  
This product is formulated to be compliant with the California Proposition 65 regulation. It contains no zinc, lead, cadmium, or other heavy metals. This product is formulated to be phthalate-free.

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)