

Interlam™

EcoMatte™

Interlam™ EcoMatte™ is a 1.6 mil (40µ) PP laminating film with a Matte finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with siliconised PE. Interlam™ EcoMatte™ is phthalate-free and provides excellent image enhancement and moisture protection for indoor graphics. It has been internationally approved for direct food contact.

- IDEAL FOR POP DISPLAYS, INDOOR AND SHORT-TERM OUTDOOR SIGNAGE, ARCHITECTURAL RENDERINGS, MAPS, AND OTHER INDOOR PROMOTIONAL GRAPHICS USED UNDER DIRECT LIGHT
- SUITABLE FOR FOOD PACKAGING, FOOD SHELVES AND OTHER APPLICATIONS WITH DIRECT FOOD CONTACT

NOT RECOMMENDED FOR LAMINATING VINYL BANNERS OR OTHER APPLICATIONS WHERE THE LAMINATE WILL BE REQUIRED TO EXPAND AND CONTRACT WITH THE PRINT MEDIA.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Clear PP
Adhesive	Aqueous Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PE Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	1.6 mil (40µ) 2.6 mil
Adhesive Layer	1 mil (25µ) (65µ)
Film/Adhesive Ratio	1 mil (25µ)
UV Protection	Yes
Outdoor Durability	Not Applicable
Service Temperature Range	-13°F to 302°F (-25°C to 150°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013