

MHL™ Impervo™ is a PET thermal laminating film with a non-reflective surface, low melt-point adhesive and a UV cured hard top coat designed to offer maximum scuff and scratch resistance. It offers excellent glare reduction and aesthetic appeal under bright light conditions. The film is resistant to water, oil, acid, and alkali and can be die cut. A 5 mil (125µ) and 10 mil (254µ) version are available.

- IDEAL FOR TRADESHOW GRAPHICS
- PERFORMS WELL IN HIGH-TRAFFIC AREAS
- SUITABLE FOR POP DISPLAYS THAT REQUIRE EXTRA DURABILITY

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT CHARACTERISTIC

Film Thickness	5 mil (125µ)	10 mil (254µ)
Film/Adhesive Ratio	3:2	7:3
Processing Temperature	185°F to 195°F (85°C to 91°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013