

Low Temperature Matte

MHL™ Low Temperature Matte is a high clarity, abrasion-resistant PET thermal laminating film with a low melt-point adhesive designed for high-speed single- and double-sided lamination. This overlamine is specifically engineered with UV inhibitors to reduce image fading and protect against moisture. Its low sealing temperature preserves inks in digitally printed graphics, which can deteriorate at high temperatures. The film is resistant to water, oil, acid, and alkali and can be die cut. A 3 mil (75µ) and 5 mil (125µ) version are available.

- IDEAL FOR A WIDE VARIETY OF POP DISPLAYS
- INCREASES RIGIDITY AND STRENGTH OF MEDIA
- PRESERVES GRAPHIC IMAGES OVER TIME

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT CHARACTERISTIC

Film Thickness	3 mil (75µ)	5 mil (125µ)
Film/Adhesive Ratio	0.5:2.5	2:3
Processing Temperature	185°F to 195°F (85°C to 91°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013