

MediaTac™ is a 0.5 mil (12µ) clear PET film, coated on both sides with a pressure sensitive acrylic adhesive, one of which is protected by a bleached clay coated Kraft paper siliconized on both sides with a differential release. The adhesive is self-wound on the release liner.

- DEVELOPED FOR PHOTO LABS WHERE A HIGH GRADE OF MOISTURE STABILITY WITHIN THE MOUNTING FILM IS REQUIRED
- IDEAL FOR HIGH-VOLUME MOUNTING, INCLUDING PRE-COATING BOARDS AND IMAGE DECAL APPLICATIONS
- RECOMMENDED FOR MOUNTING PRINTS TO SMOOTH, POROUS SUBSTRATES, SUCH AS WHITE DISPLAY BOARD, FOAM BOARDS, GATORFOAM™ AND TEMPERED HARDBOARD

PRODUCT STRUCTURE

Adhesive	Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side Clay Coated, 2 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	0.5 mil (12µ)	2.5 mil (62µ)
Adhesive Layer	1 mil (25µ) on each side	
Adhesive pH	Neutral	
UV Protection Factor	Not Applicable	
Outdoor Durability	Not Applicable	
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

For more information,
performance and warranty
guidelines please contact your
local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013