

Protac™

Sheentex™

Protac™ Sheentex™ is a 4 mil (100µ) monomeric calendared PVC laminating film with a satin pebble finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconised on the release side. Both the film and adhesive contain UV stabilisers, which protect against UV degradation.

- HOLDS A LOW POTENTIAL SLIP RATING, MAKING IT AN IDEAL CHOICE FOR USE WITH A TWO-PART FLOOR GRAPHIC SYSTEM
- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN HIGH-TRAFFIC INDOOR DISPLAY AREAS
- IDEAL FOR LAMINATING PLACEMATS, COUNTER MATS AND OTHER SIMILAR APPLICATIONS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Satin Pebble Monomeric Calendared PVC
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconised Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)
Adhesive Layer	1 mil (25µ)
UV Protection Factor	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	5 Years
Slip Rating	Low Slip Potential; Dry: 68; Wet: 41 (EN 13036-4)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Application Temperature	>41°F (5°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com