

SpotOn®

White Matte

with Interlam™ Pro Emerytex®

SpotOn® White Matte is a 100µ (4 mil) printable matte monomeric PVC film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates.

Interlam™ Pro Emerytex® is a 4 mil (100µ) monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- THE PAIRED SOLUTIONS CARRIES SEVERAL SLIP RATINGS & CERTIFICATIONS



SpotOn
(Eco) Solvent
Latex
UV



Widths up to 54in



INTERIOR*

* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PAIRED FLOOR GRAPHIC SOLUTION TECHNICAL SPECIFICATIONS

SpotOn® White Matte

PRODUCT STRUCTURE

| | |
|----------------------|---|
| Film | Matte White Monomeric PVC |
| Adhesive | Dot Pattern Removable Polyacrylate |
| Release Liner | 135 gsm Siliconized 1 Side Bleached Clay Coated Kraft |

SpotOn® White Matte

PRODUCT CHARACTERISTIC

| | |
|----------------------------------|-------------------------------|
| Film Thickness | 4.0 mil (100µ) 4.5 mil |
| Adhesive Layer | 0.5 mil (13µ) (113µ) |
| Fire Ratings | B1 (DIN 4102-1) |
| Application Temperature | >41°F (5°C) |
| Service Temperature Range | -4°F to 149°F (-20°C to 65°C) |

Interlam™ Pro Emerytex®

PRODUCT STRUCTURE

| | |
|----------------------|--|
| Film | Matte Pebble Textured Monomeric PVC |
| Adhesive | Acrylic (Pressure Sensitive) |
| Release Liner | 2 Side PE Coated, 1 Side Siliconised Kraft |

Interlam™ Pro Emerytex®

PRODUCT CHARACTERISTICS

| | |
|----------------------------------|---|
| Film Thickness | 4 mil (100µ) 5 mil |
| Adhesive Layer | 1 mil (25µ) (125µ) |
| Fire Ratings | Class 0 (BS 476 Part 6 and 7) Class 1 or A (ASTM E-84) |
| FDA Certification | PASS (FDA 21 CFR 177.1975) |
| Slip Certifications | Low Slip Potential (EN 13036-4) R 11 (DIN 51130:2010) Dry: 62; Wet: 35 (HB198:2014 (AS/NZS 4586)) Acceptable (ANSI B101.3) |
| Application Temperature | >-4°F (-20°C) |
| Service Temperature Range | -4°F to 203°F (-20°C to 95°C) |

| | |
|---------------------------|--|
| Shelf Life | 1 year |
| Storage Conditions | 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity |

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com