

Polar®

Smooth 150

Our 6 mil (150µ), white polymeric printable PVC film with removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.

Dimensionally stable, Polar® Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. It also has a removable adhesive making removal clean and easy!

- POLAR® SMOOTH 150 IS A PHTHALATE-FREE FILM
- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- POLAR® SMOOTH 150 CAN BE USED FOR WINDOW, WALL AND CONSTRUCTION TEMPORARY HOARDING APPLICATIONS

6
mil

White
Phthalate-Free
Polymeric PVC



Matte



(Eco)Solvent
Latex
UV



Removable Acrylic
Pressure-Sensitive
Adhesive



Widths up to 60 in



INTERIOR & EXTERIOR

EASY APPLICATION AND REMOVAL



APPLICATIONS

WINDOW HOARDING
CONSTRUCTION HOARDING
POINT OF SALE GRAPHICS
INTERIOR DÉCOR
DECALS & STICKERS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Polar[®]

Smooth 150

Polar[®] Smooth 150 is a 6 mil (150 μ) self-adhesive, printable matte white PVC film. It is coated with a pressure-sensitive, removable aqueous acrylic adhesive which is protected by a 78# white Kraft release paper coated on both sides with PE and siliconized on the release side. Available in 54" and 60" width master rolls, slit as instructed.

- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, GLASS, AND LOW SURFACE ENERGY SUBSTRATES.

INSTALLATION

RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

When applying Polar Smooth 150 to glass for window applications please allow 1/8" - 1/4" of exposed glass around the entire image to ensure proper adhesion to the surface.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2022 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	Removable Acrylic Pressure-Sensitive
Release Liner	78# PE Coated

PRODUCT CHARACTERISTICS

Film Thickness	6 mil (150μ)	7.2 mil
Adhesive Layer	1.2 mil (30μ)	(180μ)
Film/Adhesive Ratio	6:1.2	
UV Protection Factor	Not Applicable	
Outdoor Durability	5 Years (Ink Dependent)	
Application Temperature	-5°F (-20°C)	
Service Temperature Range	-40°F to 212°F (-40°C to 100°C)	
Flame Ratings	Class 0 (BS 476 - Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com