

PRODUCT NAME:

Polar PET 170

STANDARD:

Adhesive Compatibility & Durability

Internal Surface	Duration	Peel-Ability
Polished Concrete	Up to 1 Year	Clean
Painted Concrete	Up to 3 Months	Clean
Resin Flooring (Retail)	Up to 1 Year	Clean
Sealed Tiles	Up to 1 Year	Clean
Laminate Flooring	Up to 1 Year	Clean
Parquet Flooring	Up to 6 Months	Clean
Short-Pile Carpet	Up to 1 Year	Clean

NOT RECOMMENDED

- Porous Tiles
- Porous Concrete
- Marble Flooring
- Linoleum/Vinyl Flooring
- Long-Pile Carpet
- Indoor Sports Courts

PLEASE NOTE: the cleanliness of the removal can be affected by how clean the surface was prior to application. It is always recommended to start with a clean and dry surface. Hot water and detergent or alcohol can remove any adhesive residue. We always recommend to test a small area prior to full production and installation.

For more information, performance and warranty guide lines please contact your local Drytac office.

These test results are not transferable and may not be relevant or applicable to real life applications. Therefore, Drytac[®] strongly recommends and other regulatory entities may require additional testing to determine the suitability for any specific end application. Refer to Drytac[®] Terms and Conditions of Sale at www.drytac.com for additional liability limitations. This certificate is the property of Drytac[®] Corporation. This certificate and all copies should be returned to Drytac[®] upon request.

© 2022 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners. 10212021

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013