

# SpotOn®

SynTac™

ENVIRONMENTALLY FRIENDLY GRAPHICS

SpotOn® SynTac™ is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized Kraft PE coated release liner. This high quality, ink receptive white synthetic paper was specifically developed with the environment in mind. SpotOn® SynTac™ allows for easy, bubble-free application of vibrant graphics.

- IDEAL FOR "ENVIRONMENTALLY FRIENDLY" EASY TO INSTALL GRAPHICS
- GRAPHICS FOR SEASONAL PROMOTIONS APPLICATIONS
- SHORT-TERM WALL AND WINDOW APPLICATIONS



Product Code: SPSF

**120** White  
micron Matte  
PP



Latex  
UV



Removable  
DOT Pattern Polyacrylate  
Adhesive



Width 1370mm

YEARS DURABILITY  
**2**

INTERIOR

MONTHS DURABILITY  
**6**

EXTERIOR

## APPLICATIONS

- MOUNT TO BOARDS
- WINDOW GRAPHICS
- TEMPORARY SALES SIGNAGE
- PRESENTATIONS
- POP & EVENT SIGNAGE



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# SpotOn®

## SynTac™

SpotOn® SynTac™ is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconised Kraft PE coated release liner. This high quality, ink receptive white synthetic paper was specifically developed with the environment in mind. SpotOn® SynTac™ allows for easy, bubble-free application of vibrant graphics.

- IDEAL FOR "ENVIRONMENTALLY FRIENDLY" EASY TO INSTALL GRAPHICS
- GRAPHICS FOR SEASONAL PROMOTIONS APPLICATIONS

\*\*Please note: ink dependant for outdoor durability.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

120524

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte White PP
<b>Adhesive</b>	Removable Dot Pattern Polyacrylate
<b>Release Liner</b>	140 gsm 1 Side Siliconised PE Coated Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	4.8 mil (120µ)	5.3 mil (133µ)
<b>Adhesive Layer</b>	0.5 mil (13µ)	
<b>Outdoor Durability</b>	6 months**	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	-4°F to 149°F (-20°C to 65°C)	
<b>Fire Rating</b>	Class B (EN 13501-1)	
<b>Shelf Life</b>	1 year	
<b>Storage Conditions</b>	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)