

## Pro Anti-Graffiti

Interlam™ Pro Anti-Graffiti is a 0.8 mil (20µ) high performance PCTFE film with strong anti-graffiti characteristics and a pressure sensitive acrylic adhesive that is protected by a siliconized PE coated paper release liner. The film is flame resistant and provides a high degree of resistance to ultraviolet light, dirt and pollutants, and the gloss finish offers superb clarity, detail and color contrast. It wipes clean of virtually any spray paint and can be cleaned with most solvents and detergents without adverse effect. The premium adhesive creates a strong bond to UV inks as well as latex and other ink technologies.

- IDEAL FOR RETAIL ADVERTISING GRAPHICS, EVENT GRAPHICS OR DISPLAYS WHERE GRAFFITI MIGHT BE A POSSIBILITY, SUCH AS OUTDOOR BUS SHELTERS, TRAIN STATIONS AND KIOSKS
- CAN BE USED FOR CONSTRUCTION BARRICADE APPLICATIONS
- CAN BE USED FOR LONG-TERM EXTERIOR APPLICATIONS.

Please note: for install, the material must be kept at a minimum +41°F (+5°C) and the surface should always be tested prior to install.

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	High Performance PCTFE
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconized PE Coated Paper

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	0.8 mil (20µ)   2 mil
<b>Adhesive Layer</b>	1.2 mil (30µ)   (50µ)
<b>Film/Adhesive Ratio</b>	0.8:1.2
<b>UV Protection</b>	Yes
<b>Outdoor Durability</b>	7 Years
<b>Fire Rating</b>	Class 0
<b>Application Temperature</b>	-4°F (-20°C)
<b>Service Temperature Range</b>	-49°F to 230°F (-45°C to +110°C)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013