Interlam[™]

Pro Matte

TECHNICAL SPECIFICATION

Interlam™ Pro Matte is a 75µ (3 mil) monomeric soft calendared PVC laminating film with a matte finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with PE and siliconised on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE WHERE A NON-GLARE FINISH IS REQUIRED OR WHERE SPECIFIC LIGHTING CONDITIONS CANNOT BE CONTROLLED
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, EVENT SIGNAGE AND PHOTOGRAPHIC IMAGES
- INTERLAM™ PRO MATTE HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film

Matte Monomeric Soft
Calendared PVC

Adhesive

Acrylic (Pressure Sensitive)

1 Side PE Coated

PRODUCT CHARACTERISTICS

Film Thickness	3 mil (75μ) • 4 mil
Adhesive Layer	1 mil (25μ) (100μ)
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	5 Years (Ink Dependent)
Fire Rating	Class 0
Application Temperature	>41°F (20°C)
Service Temperature Range	-13°F to 302°F (-25°C to 150°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Roller Laminator
Room temperature
to 104°F (40°C)

Press

Not recommended



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com Tel: +44 (0) 117 958 6500

Canada

30 Driver Road, Brampton, Ontario, L6T 5V2, Canada toronto@drytac.com Tel: +1 800.353.2883

USA

5601 Eastport Boulevard, Richmond, Virginia, 23231, USA customerservice@drytac.com

Tel: +1 800.280.6013