

Polar®

Choice Clear P

Polar® Choice Clear P is the ideal choice for a printable monomeric PVC film. Available with a gloss or matte finish with a permanent adhesive, Polar® Choice Clear P maximises adhesive performance on a wide variety of substrates.

Polar® Choice Clear P is outdoor durable for up to 5 years and is ideal for longer-term signage and general advertising applications, including windows, POP displays, stickers and decals.

- IDEAL FOR LONG-TERM INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- WINDOW GRAPHICS
- SUITABLE FOR MANY APPLICATIONS

70
micron

Clear
Monomeric
PVC

Gloss or
Matte



(Eco) Solvent
Latex
UV



Permanent
Acrylic Solvent
Adhesive



Widths up to 1524mm



5 YEARS DURABILITY
INTERIOR & EXTERIOR
(unprinted)

THE CHOICE FOR MONOMERIC PVC



APPLICATIONS

GENERAL SIGNAGE
WINDOW GRAPHICS
EXHIBITION GRAPHICS
POS DISPLAY



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

Polar®

Choice Clear P

Polar® Choice Clear P is an 70µ (2.8 mil) gloss or matte clear monomeric PVC film, coated on one side with a permanent, pressure sensitive clear solvent acrylic adhesive that is protected by a 140gsm 2 side PE coated release liner. Suitable for interior and exterior use (up to 5 years).

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY SMOOTH SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2022 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Clear Gloss or Matte Monomeric PVC
Adhesive	Clear Permanent Solvent Acrylic (Pressure Sensitive)
Release Liner	140gsm 2 side PE Coated Release Paper

PRODUCT CHARACTERISTIC

Film Thickness	2.8 mil (70µ) 3.8 mil
Adhesive Layer	1 mil (25µ) (95µ)
Outdoor Durability	5 Years (Unprinted)
Fire Rating (EN 13501-1)	Class C-s1,d0
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Choice, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Choice are Drytac's Dynamic™, Interlam™ or Protac™ overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013