

# SteriTac®

## Antimicrobial Film

SteriTac® Film is a 150µ (6 mil) textured polyester film incorporating Microban® antimicrobial protection. When microbes meet the Microban® reservoirs in the film, the cell wall of the microbes is disrupted. The result is a film surface providing constant additional protection against the spread of microbial contamination. SteriTac® Film offers reliable protection from mould growth and bacterial contamination, including MRSA, Streptococcus, E.coli, Salmonella and more. SteriTac® Film is ideal for use in environments where hygiene is of particular importance, such as schools, nurseries, restaurants/cafeterias and hospitals. The film's textured finish gives it good resistance to abrasions, while its clarity ensures that no colours are diminished.



**Drytac**  
Protective  
Film

**Product Code: PAB**

**150**  
micron

Clear Textured PET  
with Antimicrobial  
Hard Coating

Matte



**Not a  
Printable  
Film**



**Solvent  
Acrylic  
Adhesive**



**Widths up to 1200mm**



**ANTIMICROBIAL  
PROTECTION**



**INTERIOR**



**EXTERIOR**

**WITH ADDITIONAL  
MICROBAN® ANTIMICROBIAL PROTECTION**



**EFFECTIVE  
AGAINST  
CORONAVIRUS  
FOR 15 YEARS\***  
TESTED TO ISO 21702\*

## APPLICATIONS

IDEAL FOR PREVENTING THE GROWTH AND SPREAD OF BACTERIA FROM TOUCH SURFACES, COUNTERS, CONTROL PANELS, DOOR PLATES, SWITCHES AND EQUIPMENT.



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# SteriTac®

## Antimicrobial Film

SteriTac® Film is a 150µ (6 mil) textured hard coat PET film with a durable Microban® antimicrobial agent that offers reliable protection against mould and mildew growth and bacterial degradation of the film. The reverse side of the film is coated with a pressure sensitive, acrylic adhesive that is protected by a 100gsm 2 sided PE coated kraft release liner. The film provides scratch and chemical resistance to withstand daily cleaning methods.

- PVC-FREE, PLASTICISER-FREE AND HALOGEN-FREE
- THE PRIMARY PURPOSE OF INCLUDING MICROBAN® IS TO PROTECT THE FILM ITSELF AND TO INCREASE ITS EFFECTIVE LIFETIME AGAINST ATTACK FROM MOULD AND MILDEW ETC. NORMAL CLEANING AND STERILISATION PRACTICES SHOULD STILL BE ADHERED TO, IN ORDER TO REMOVE POTENTIALLY BIOLOGICALLY ACTIVE CHALLENGES SUCH AS AEROSOL DROPLETS FROM BREATHING ETC.
- THE USE OF AQUEOUS BASED SANITISERS INCORPORATING BLEACH AND QUATERNARY SURFACTANTS ARE PREFERRED TO THE USE OF SOLVENTS NOT ONLY FOR HEALTH SAFETY AND ENVIRONMENTAL REASONS, BUT TO ALSO ENHANCE THE PRODUCT LIFE TIME OF THE FILM.

\*Antiviral activities of SteriTac® Protection film surface and non-active surface have been tested under conditions defined by the ISO 21702 (2019) protocol for a contact time of 15 and 60 minutes against Human Coronavirus SARS-CoV-2, changes in environments and locations can provide different results so it is important that hygiene and cleaning regimes remain in place.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2022 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

04032022

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Textured PET with Microban® Antimicrobial Hard Coating
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	100gsm 2 Sided PE Coated; 1 side Siliconised Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	6.0 mil (150µ)	7.0 mil (175µ)
<b>Adhesive Layer</b>	1.0 mil (25µ)	
<b>UV Protection</b>	Yes	
<b>Slip Rating</b>	Moderate Slip Potential; PTV Wet: 29 (EN 13036-4)	
<b>Chemical Resistance</b>	Excellent resistance to many common industrial solvents and household chemicals	
<b>Antimicrobial Properties</b>	<b>15 Year Antimicrobial Protection;</b> tested against JIS Z2801; Please see SteriTac Antimicrobial Properties document for more info.	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	5°F to 248°F (-15°C to 120°C)	
<b>Shelf Life</b>	2 Years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013

www.drytac.com

#### PRODUCT NAME: SteriTac® Film

Description	Microbial Test	Microbe Class	Test Result*	Test Method <small>Harmonised JIS Z2801/AATCC 100</small>
SteriTac® Antimicrobial Protection Film	MRSA	Bacteria Medical	Biocidal Pass	Unprocessed Film Sample
	Streptococcus Faecalis	Bacteria Medical	Biocidal Pass	
	Pseudomonas Aeruginosa	Bacteria Medical	Biocidal Pass	
	Klebsiella Pneumonia	Bacteria Medical	Biocidal Pass	
	Listeria Monocytogenes	Bacteria Food	Biocidal Pass	
	E.coli 0157	Bacteria Food	Biocidal Pass	
	Salmonella Enteritidis	Bacteria Food	Biocidal Pass	
	Bacillus Cereus	Bacteria Food	Biocidal Pass	
	Aspergillus Niger	Fungi (Black Mold)	Biocidal Pass	
	Penicillium Purpurogenum	Fungi (Black Mold)	Biocidal Pass	
	Saccharymyces Cerevisiae	Fungi Yeast	Biocidal Pass	
	Phoma Violacea	Fungi	Biocidal Pass	
	Simulated Wear Test	MRSA	Bacteria Medical	
E.coli 0157		Bacteria Food	Biocidal Pass	
Simulated Embossed Sample	MRSA	Bacteria Medical	Biocidal Pass	Samples were stretched 20% in both MD/CD direction to simulate process of embossing (an embossed sample cannot undergo anti-microbial testing).
	E.coli 0157	Bacteria Food	Biocidal Pass	
15 Year Lifetime Test	MRSA	Bacteria Medical	Biocidal Pass	Samples were tested by an independent lab using standard test protocols that simulate real life cleaning procedures over a period of 15 years.
	E.coli 0157	Bacteria Food	Biocidal Pass	
	Aspergillus niger	Fungi (Black Mold)	Biocidal Pass	
Ethanol, IPA, MEK, Phenol Based Disinfectant, Quaternary Ammonium Based Disinfectant, Bleach	MRSA	Bacteria Medical	Biocidal Pass	Samples were soaked for 24 hours to simulate extreme cleaning regimes before undergoing testing.
	E.coli 0157	Bacteria Food	Biocidal Pass	

\*Antimicrobial pass is considered to be a 97% kill rate.

**Please Note:** Drytac can test for a specific bacteria/fungi if not listed above.

**For more information, performance and warranty guide lines please contact your local Drytac office.**

These test results are not transferable and may not be relevant or applicable to real life applications. Therefore, Drytac® strongly recommends and other regulatory entities may require additional testing to determine the suitability for any specific end application. Refer to Drytac® Terms and Conditions of Sale at [www.drytac.com](http://www.drytac.com) for additional liability limitations. This certificate is the property of Drytac® Corporation. This certificate and all copies should be returned to Drytac® upon request.

© 2022 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013