

# ReTac®

## Clear PET

## TECHNICAL SPECIFICATIONS

ReTac® Clear PET is a 3 mil (75µ) clear printable polyester film coated on one side with ReTac® ultra removable adhesive, protected by a siliconized kraft release paper. ReTac® Clear PET offers a sustainable solution suitable for latex and UV printing, that can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- IDEAL FOR EASY TO APPLY RETAIL AND POP WINDOW GRAPHICS, NO WET INSTALL NEEDED
- RETAC CLEAR PET IS A NON-PVC SOLUTION, OFFERING A MORE ENVIRONMENTALLY FRIENDLY OPTION TO SATISFY THE RISING DEMAND FOR SUCH PRODUCTS FROM ALL CORNERS OF THE MARKET

### PRODUCT STRUCTURE

<b>Film</b>	Gloss Clear Polyester (PET)
<b>Adhesive</b>	Clear ReTac® ultra removable and repositionable adhesive technology
<b>Release Liner</b>	135gsm one side siliconised clay coated kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3.0 mil (75µ)   3.7 mil (93µ)
<b>Adhesive Layer</b>	0.7 mil (18µ)   (93µ)
<b>Outdoor Durability</b>	5 Years; 2 Years Removability (Ink Dependant)
<b>FDA Certification</b>	PASS (FDA 21 CFR 177.1630(f).(g))
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	40°F to 120°F (4.4°C to 48.9°C)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

#### Installation Recommendations:

Dry installation is recommended. Please refer to the ReTac Clear PET Application Guide for more details.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013