

# Paper Fleece

Smooth

UNIQUE & VIBRANT WALLCOVERINGS

Paper Fleece Smooth is a PVC-free, non-woven wallcovering film designed for long-term use, boasting excellent dimensional stability. Its smooth satin finish makes it perfect for creating vibrant custom wallcoverings in various settings like homes, retail stores, hotels, and offices. With a repositionable permanent adhesive and an air-egress release liner, applying it is a breeze, ensuring a bubble-free finish and allowing for easy repositioning. Plus, its photorealistic print quality produces sharp, detailed graphics with quick drying times, ideal for creating stunning, vivid designs.

- PVC-FREE WALLCOVERINGS
- REPOSITIONABLE PRESSURE SENSITIVE FOR EASY PEEL AND STICK WALL GRAPHICS AND WALLCOVERINGS
- PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS

**180** Non-Woven  
gsm Paper Fleece

■  
Satin



(Eco) Solvent  
Latex  
UV



Clear Repositionable  
Permanent Acrylic  
Adhesive



Widths up to 1370mm

5 YEARS DURABILITY  
INTERIOR



## APPLICATIONS

- HOTEL DÉCOR
- RETAIL STORES
- INTERIOR DÉCOR
- OFFICES

DRYTAC®  
**ZERO**®

www.drytac.com

# Paper Fleece

## Smooth

Paper Fleece Smooth is a user-friendly 180gsm non-woven paper fleece wallcovering film featuring a clear repositionable permanent acrylic adhesive. Protected by a 140 gsm clay-coated release liner equipped with bubble-free technology, it ensures hassle-free application and repositioning. It is also an eco-friendly solution, meeting the rising demand for sustainable products among consumers.

- IDEAL FOR WALL GRAPHICS, CUSTOM WALL MURALS, INTERIOR DÉCOR, RETAIL DISPLAYS, TRADE SHOW GRAPHICS AND SIGNAGE
- WITH ITS SUPERIOR DIMENSIONAL STABILITY, THIS PRODUCT GUARANTEES LONG-LASTING DURABILITY AND RETAINS ITS SHAPE OVER TIME, MAKING IT IDEAL FOR A MULTITUDE OF APPLICATIONS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Satin White Non-Woven Paper Fleece
<b>Adhesive</b>	Clear Repositionable Permanent (Pressure Sensitive)
<b>Release Liner</b>	140 gsm Clay Coated Release Paper with Bubble-Free Technology

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	180 gsm
<b>Adhesive Layer</b>	1.2 mil (30µ)
<b>Outdoor Durability</b>	Not Applicable
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	-4°F to 203°F (-20°C to 95°C)
<b>Fire Rating</b>	Class C-s1,d0 (EN 13501-1+A1 : 2013)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

**INSTALLATION RECOMMENDATION**  
Please see Wall Graphic Installation & Removal Instructions for further details. The surface must be clean and smooth and free of defects before application.



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013